


## ISDN terminal adapter for top-hat rail mounting T726-RS1



ITU transmission standards	X.75, V.110, V.120
Interface speed	1200, 2400, 4800, 9600, 19600, 38400, 57600 and 115200 bps autobauding
Data formats recognized	7E1, 7O1, 8N1, 8E1, 8O1
Interface	V.24 (RS232), D-Sub 9-pole
Instruction set	Extended AT instruction set
Telephone line	RJ 45 (ISDN 4-wire)
Power supply	24 VDC +15%, -30%
Current consumption	max. 60mA
24V connection	Screw terminal, 2-pole
Temperature range	0-55 °C
Humidity	0-95%, non-condensing
Dimensions	45 x 75 x 114 mm (WxHxL)
Weight	175 g
Standards	TBR3 A1 (ETS 300 012, 300 125, 300 403)



## Meaning of LEDs

<b>LED constant</b>	>>	Status display
<b>LED flashing slowly</b>	>>	Information
<b>LED flashing quickly</b>	>>	Error display

---

<b>RI Call sign</b>	Flashing slowly
LED constant	DCD connection active
LED flashing quickly	DTR off
<b>AA Auto reply</b>	Flashing slowly
LED constant	OFF HOOK
LED flashing quickly	DSR off
<b>MSN No internal 'MSN'</b>	Flashing slowly
LED flashing quickly:	Initialization error
<b>ACT ISDN active</b>	LED constant
LED flashing quickly	ISDN error
<b>Tx Send data</b>	
Data being sent to the PCD	
<b>Rx Receive data</b>	
Data being received by the PCD	

---